

MILITARY SPECIFICATION

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC,
(HERMETICALLY SEALED IN METAL, CERAMIC, OR GLASS CASES),
ESTABLISHED AND NON-ESTABLISHED RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-19978E, dated 22 November 1985,
and is approved for use by all Departments and Agencies of the Department
of Defense.

PAGE 17

4.6.2.1.1.2, delete and substitute:

"4.6.2.1.1.2 For FR levels M, P, R, and S. In addition to the tests specified in
4.6.2.1.1.1, a minimum of 10 sample units from each inspection lot (see 4.6.1.1)
shall be subjected to subgroup 4 of table XII (see 4.6.1.3.3). Allowable
failures shall be as specified in table IV of MIL-STD-690."

Custodians:

Army - ER
Navy - EC
Air Force - 85

Preparing activity:

Air Force - 85

Agent:

DLA - ES

Review activities:

Army - AR, MI
Navy - AS
Air Force - 11, 17, 99
DLA - ES

(Project 5910-1571)

User activities:

Army - AT, AV, ME
Navy - OS, MC, SH